



1071332 (K534-X202-14000) **SPRING ASSIST CLOSED**





REPAIR PARTS KITS					
DESCRIPTION	PART NO.				
INT. PARTS KIT (SPRING ASSIST CLOSED) CONSISTS OF ITEM NO. 20	1075233				
INT. PARTS KIT (SPRING ASSIST OPEN) CONSISTS OF ITEM NO. 20	(534-S)				
INT. PARTS KIT (LIMIT STOP) CONSISTS OF ITEM NO.'S 22 THRU 25	1075230 (534-LS)				
INT. PARTS KIT (LIMIT STOP / POS. INDICATOR) CONSISTS OF ITEM NO.'S 22 THRU 24 & 26 THRU 31	1075231 (534-PI)				

CONVERSION PART	TS KITS
DESCRIPTION	PART NO.
CONVERSION KIT (SPRING ASSIST CLOSED) CONSISTS OF ITEM NO 20	1075233
CONVERSION KIT (SPRING ASSIST OPEN) CONSISTS OF ITEM NO 20	(534-S)
CONVERSION KIT (LIMIT STOP) CONSISTS OF ITEM NO.'S 12 & 21 THRU 25	1071308 (K534-LSC)
CONVERSION KIT (POSITION INDICATOR) CONSISTS OF ITEM NO.'S 12, 21 THRU 24 & 26 THRU 31	1071309 (K534-PIC)

		REVISIONS		
REV	ECN	DESCRIPTION	DATE	APP'D
		SEE SHEET 1 FOR LIST OF CHANGES		


D

SPRING ASSIST CLOSED MODEL & SPRING ASSIST OPEN MODEL					
ITEM	PART NO.	MODEL	DESCRIPTION	QTY	
20	1073340	V534-170	SPRING, COMPRESSION, 534	1	

LIMIT STOP MODEL						
ITEM	PART NO.			QTY		
21	1073345	V534-420K	CAP, 1-12 VALVE LS/PI, V5	34	1	
22	1071673	ORB-018	O-RING, 2-018	BUNA N	1] (
23	1073368	V534-570	GUIDE, LS/PI, 534		1	
24	1071668	ORB-012	O-RING, 2-012, NITRILE	BUNA N	1	
25	1073373	V534-576	SCREW, LIMIT STOP, 534		1	

	LIMIT STOP POSITION INDICATOR MODEL						
ITEM	PART NO.	MODEL	DESCRIPTION		QTY		
21	1073345	V534-420K	CAP, 1-12 VALVE LS/PI, V53	CAP, 1-12 VALVE LS/PI, V534			
22	1071673	ORB-018	O-RING, 2-018	BUNA N	1		
23	1073368	V534-570	GUIDE, LS/PI, 534		1		
24	1071668	ORB-012	O-RING, 2-012, NITRILE	BUNA N	1		
26	1073362	V534-535	SHAFT, PI, 534		1		
27	1073346	V534-442	PLATE, DIAPHRAGM, UPR, 534		1		
28	1071666	ORB-006	O-RING, 2-006	BUNA N	1		
29	1081128	V534-700	SCREW, LIMIT STOP, ASSY., 534		1		
30	1073367	V534-555	ROD, PI, 534		1		
31	1073365	V534-550	PI SIGHT GLASS, 534		1		

SEE SHEET 1 FOR STANDARD NORMALLY OPEN MODEL



TRANSMISSION OF THIS DOCUMENT OR DETAILS

CONTAINED HEREIN, IN PART OR IN WHOLE, IS PROHIBITED WITHOUT THE WRITTEN CONSENT OF AQ-MATIC ENGINEERING. THIS DOCUMENT AND ANY COPIES SHALL BE RETURNED TO AQ-

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M -1994

MATIC UPON WRITTEN REQUEST.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES [mm]
CORNER FILLETS R.005-.020 [.127-.508]

TOLERANCES: ±1°
1 PLACE X: ±.100 [2.54]
2 PLACE XX: ±.010 [0.25]
3 PLACE .XXX: ±.005 [0.13]