

RE	REPAIR PARTS KITS					
DISCRIPTION	PART NO.					
	1070107 (AV4-RA)	1070502 (AV4-RAHT)				
DIAPHRAGM & SEALS KIT CONSISTS OF ITEM NO'S 6, 7, 9, 11, 12, 14, 15, 16	INCLUDES DISC 1074234 (424-JH) DIAPHRAGM 1074222 (424-FB)	INCLUDES DISC 1074235 (424-JT) DIAPHRAGM 1074224 (424-FV)				
INT. PARTS KIT (NORM. OPEN) CONSISTS OF STANDARD ITEM NO'S 5(2), 8, 10, 17	107011	9 (424-RF)				
SEAT (ITEM NO. 13)	107424	5 (424-MO)				

ASSEMBLY TOOLS				
DESCRIPTION	PART NO.			
FOR INSTALLATION & REMOVAL OF SEAT (ITEM NO. 13) (TOOL NOT SHOWN)	1074247 (424-MT)			
FOR INSTALLATION AND REMOVAL OF SHAFT GUIDE (ITEM#7) 3/4" HEX. SOCKET DRIVER	1074227 (424-GT)			

NOTE:

- 1. AMERICAN NATIONAL STANDARD TAPER PIPE THREADS (NPT) PER ANSI B2.1-1968
- 2. VALVES AVAILABLE WITH B.S.P.T. END CONNECTIONS.





REVISIONS					
ECN	REV.	DESCRIPTION	DATE	APP'D	
1823	1/20/21	TRK			
2139	9/20/22	TRK			
2171 N REPLACED 1074226 (SHAFT GUIDE) WITH 43852				TRK	
2271	2271 P REMOVE DISC 1074235 FROM BOM				

ITEM NO.	DESCRIPTION			STD.	PART NUMBER	QTY.
	MACHINED BODY CAST		1-1/4" NPT	*	1074196 (424-A5)	
		OAOT IDON	1-1/2" NPT	*	1074199 (424-A6)	1
1		CAST IRON	1-1/4" BSPT		1074197 (424-A5-BSPT)	
			1-1/2" BSPT		1074200 (424-A6-BSPT)	
2	CAP, NPT TAP T	OP	CAST IRON	*	1074202 (424-C)	1
3	HEX NUT 1/4" -	20	PLATED STEEL	*	1071656 (NUZ-0008)	4
4	HEX SCREW 1/4"	- 20	PLATED STEEL	*	1072399 (SCZ-0007)	4
5	DIAPHRAGM PLA	ATE	STAINLESS STEEL	*	43943	2
6	HEX NUT 5/16 - 24		STAINLESS STEEL	*	1263853 (RMET)	1
7	DIAPHRAGM, 424		BUNA N	*	1074222 (424-FB)	1
/			FKM		1074224 (424-FV)	
8	SHAFT GUIDE (REQ'S ASSY TOOL)		STAINLESS STEEL	*	43852	1
9	O-RING 2-132		FKM	*	1071806 (ORV-132)	1
10	NORMALLY OPEN COM	BO SHAFT	STAINLESS STEEL	*	44013	1
11	DISC		HYCAR	*	1074234 (424-JH)	1
12	HEX NUT (1/4"-2	28)	STAINLESS STEEL	*	1263852 (NUS-0010)	1
13	SEAT - BRASS (REQ'S A	SSY TOOL)	BRASS	*	1074245 (424-MO)	1
14	COPPER GASK	ET	COPPER	*	1074252 (424-R)	1
15	O-RING 2-110		AFLAS	*	1071661	1
16	O-RING 2-028		FKM	*	1071793 (ORV-028)	1
17	DISC PLATE		STAINLESS STEEL	*	43942 (424-H)	1

TORQUE TABLE				
ITEM#	DESCRIPTION	TORQUED TO (+/- 10%)		
13	SEAT	120 IN/LBS		
12	LOWER NUT	90 IN/LBS		
8	SHAFT GUIDE	120 IN/LBS		
6	UPPER NUT	90 IN/LBS		
3 & 4 NUT & CAP SCREW		90 IN/LBS		

	THE COMPONENT OR PR	ODUCT DESCRIB	ED IN THIS DOC
THIS DOCUMENT IS SOLELY THE PROPERTY OF AQ-MATIC REPRODUCTION, USE DISCLOSURE, OR TRANSMISSION OF THIS DOCUMENT OR DETAILS CONTAINED HEREIN, IN PART OR IN WHOLE, IS PROHIBITED WITHOUT THE WRITTEN CONSENT OF AQ-MATIC ENGINEERING. THIS DOCUMENT	THIRD ANGLE PROJECTION		2
AND ANY COPIES SHALL BE RETURNED TO AQ- MATIC UPON WRITTEN REQUEST.	APPROVALS	DATE	Day
INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M -1994 UNLESS OTHERWISE SPECIFIED:	DRAWN TRK	1/20/21	DESCRIPTIC C
DIMENSIONS ARE IN INCHES [mm] CORNER FILLETS R.005020 [.127508] TOLERANCES: ANGLES: ±1°	CHECKED BY		SIZE C
1 PLACE .X: ± .100 [2.54] 2 PLACE .XX: ± .010 [0.25] 3 PLACE .XXX: ± .005 [0.13]	APPROVED		SCALE -

Buy II a Mattic. Completed in this document must comply with Rohs 3 EU (EUROPEAN UNION) DIRECTIVE 2015/863

Buy II a Mattic. Complete in this document must comply with Rohs 3 EU (EUROPEAN UNION) DIRECTIVE 2015/863

Buy II a Mattic. Complete in this document must comply with Rohs 3 EU (EUROPEAN UNION) DIRECTIVE 2015/863

Buy II a Mattic. Complete in this document must comply with Rohs 3 EU (EUROPEAN UNION) DIRECTIVE 2015/863

CATALOG SHEET, VAV4, DIAPHRAGM VALVE

SIZE C DWG NO. 1077636 P

SCALE 1:2 SOLIDWORKS FORMAT SHEET 1 OF 2

	CONVERSION KITS				
	DESCRIPTION	PART NO.			
CONVEI CLOSED IT	RSION KIT (SPRING ASSIST) CONSISTS OF STANDARD EM NO'S 20 THRU 25	1074266 (424-SCC)			
CONVEI OPEN)	RSION KIT (SPRING ASSIST CONSISTS OF STANDARD EM NO'S 8, 14, 26, 27	1074269 (424-SOC)			


1074265 (424-SC)

1074268 (424-SO)

CONVERSION KITS	3
DESCRIPTION	PART NO.
CONVERSION KIT (SPRING ASSIST CLOSED) CONSISTS OF STANDARD ITEM NO'S 20 THRU 25	1074266 (424-SCC)
CONVERSION KIT (SPRING ASSIST OPEN) CONSISTS OF STANDARD ITEM NO'S 8, 14, 26, 27	1074269 (424-SOC)

INT. PARTS KIT (SPRING ASSIST OPEN) CONSISTS OF STANDARD

ITEM NO'S 14, 26, 27




1072472 (VAVD-0002-90000)(1-1/4" NPT)	
1072477 (VAVE-0002-90000)(1-1/2" NPT)	
SPRING ASSIST CLOSED	

	TORQUE TABLE				
ITEM #	DESCRIPTION	TORQUED TO (+/- 10%)			
21	RETAINER NUT	120 IN/LBS			
24	CENTERING NUT	90 IN/LBS			

	REVISIONS				
ECN	REV.	DESCRIPTION	DATE	APP'D	
1823	L	CATALOG SHEET UPDATE, COMPONENT CHANGES	1/20/21	TRK	
2139	М	9/20/22	TRK		
2171	N	REPLACED 1074226 (SHAFT GUIDE) WITH 43852	1/26/23	TRK	
2271	2271 P REMOVE DISC 1074235 FROM BOM			TRK	

	NORMAL	LY CLOSED M	ODEL		
ITEM NO.				PART NUMBER	QTY.
18	NORMALLY CLOSED COMBO SHAFT	STAINLESS STEEL	*	44013-02 (424-LL)	1
19	PIPE PLUG (1/4" NPT)	PLATED STEEL	*	1071918 (PLZ-0008)	1
	SPRING AS	SIST CLOSED	MODE	EL	
ITEM NO.	DESCRIPTION		STD	PART NUMBER	QTY.
20	CAP, SPRING ASSIST CLOSED	CAST IRON	*	1074208 (424-CC)	1
21	RETAINER NUT	BRASS	*	1074274 (424-TT)	1
22	O-RING, 2-020	BUNA-N	*	1071674 (ORB-020)	1
23	SPRING	STAINLESS STEEL	*	1074270 (424 SS)	1
24	CENTERING NUT	STAINLESS STEEL	*	1074276 (424-X)	1
25	PIPE PLUG (1/8" NPT)	BRASS	*	1071903 (PLB-0007)	1
	SPRING A	SSIST OPEN N	IODEL	-	
ITEM NO.			STD	PART NUMBER	QTY.
26	DIAPH. PLATE, 424	STAINLESS STEEL	*	43728	1
27	SPRING	STAINLESS STEEL	*	1236766	1

SEE SHEET 1 FOR STANDARD NORMALLY OPEN MODEL



(1/4" NPT)

(26)

4500197 (VAVD-0030-90000)(1-1/4" NPT) 1072479 (VAVE-0030-90000)(1-1/2" NPT) NORMALLY CLOSED

1072471 (VAVD-0001-90000)(1-1/4" NPT) 1070064 (VAVE-0001-90000)(1-1/2" NPT) SPRING ASSIST OPEN